

## Sunlast – outstanding color fastness

A pigmented acrylic fiber that resists sunlight and weathering while maintaining maximum color fastness.

## Properties

- Sunlast is a pigment-dyed acrylic fiber designed to resist sunlight and weather exposure with maximum color persistence
- Sunlast uses only high-performance pigments to ensure top color fastness even under aggressive outdoor environment
- Sunlast is produced in a broad range of attractive colors
- Sunlast resists repeated cycles of weather exposure including wetting and drying while maintaining their mechanical performance. Strong, uniform and permanent pigment binding to fiber prevents bleeding and maximizes color depth
- Sunlast is environmental friendly and safe; using only non-toxic pigments

## Applications

Sunlast is suitable for just about any application where resistance to color fading is a major requirements:

- Awnings
- Boat covers
- Car tops
- Garden furniture
- Car interiors
- Upholstery



## Material data of Sunlast

Typical properties	Units	L28
Fineness	dtex	2.2
Tenacity	g/dtex	>3.1
Elongation	%	35.5
		Standard ISO 105-B02: 7+
Light fastness		on the blue wool scale
		Standard ISO 105-B04: 7+ on the blue wool scale Standard AATCC 169/1 ("Florida test"), 2000 hours:
Weather fastness		4 or better on the gray scale







Composites – Fibers & Materials | SGL Composites S.A. marketing.pt@sglcarbon.com www.sglcarbon.com 03 2024/0 2NÄ Printed in Germany

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our "General Conditions of Sale".